



## Bevolo Gas & Electric Lights Wind Guard Installation Instructions

Bevolo's Wind Guard is a compact design that is user friendly and easy to install with minimal effort and tools. Each Bevolo Wind Guard kit is a simple, one piece assembly that requires only minutes to install.

Recommended tools: 7/16" open end wrench and a pair of pliers.

**Please note: Pipe joint compound MUST be used when assembling all threaded pieces.**

Step 1: Turn gas valve to off position to extinguish flame and allow burner assembly to cool before handling. Using a 7/16" wrench remove gas tip (pliers may be required to hold brass coupler in place while removing tip). Also, remove brass coupler that connects gas tip to valve stem. Discard brass coupler **only**; the gas tip will be reused.

Step 2: Screw the recently removed gas tip into brass coupler located inside of Wind Guard. After tip is finger tight, use 7/16" wrench to tighten the rest of the way.

Step 3: Screw Wind Guard assembly onto burner valve stem until finger tight. Grip brass coupler underneath Wind Guard with pliers and tighten assembly until snug. Make sure slit in gas tip is aligned parallel to front of gas fixture.

Step 4: Return gas valve to open position and relight burner. Bevolo recommends flame height to be 1" - 1 1/2" for smaller fixtures.



Before



Assembly out of box



After